

The KM 634 is a robust and powerful tool for logs – especially for heavy duty operation. Well suited for handling single trunks.

- ▶ **Low height** with one horizontal hydraulic cylinder – especially when closed due to the interlocking arms.
- ▶ **Long service life** is ensured by the sturdy construction, high quality components and generously dimensioned bearing system. All bearing bolts are case hardened and housed in steel bearing bushes.
- ▶ **Optimised design** allows extremely small grapple diameter – ideal for handling thin timber securely. The arms open almost vertically. That enables an easy penetration into the timber stack.
- ▶ **Synchronisation** of arms due to sturdy compensation rods.
- ▶ **Protection of the hoses** for the hydraulic connections by a hose guard on the KINSHOFER rotator.
- ▶ **Precise positioning** of the loads is no problem in combination with the KINSHOFER rotator – continuous rotation, precise start and stop ability.
- ▶ **Safety** is assured in the event of an unexpected pressure drop due to the integrated non-return valve.
- ▶ **Reinforced version KM 634S** with more sturdy construction and equipped with a stronger rotator.



KM 634-0.25

Packages logging grapple KM 634 c

Type	Capacity	Width E	min. Log-Ø D2	max. Log-Ø D1	Opening A max.	Weight	Closing force	Load capacity
	(m ²)	(mm)	(mm)	(mm)	(mm)	(kg)	(kN)	(kg)
KM 634-0.25 c	0,25	420	90	460	1470	215	13	4000
KM 634-0.35 c	0,35	500	135	590	1950	300	16	5000

Package consists of: logging grapple, rotator with hose guard (for KM 634-0,25: KM 06 F173-35, for KM 634-0,35: KM 10 F173-35), short connecting hoses KM 203 01, upper suspension KM 501 suiting rotator size, non-return valve

Logging grapple KM 634

Type	Capacity	Width E	min. Log-Ø D2	max. Log-Ø D1	Opening A max.	Weight	Closing force	Load capacity
	(m ²)	(mm)	(mm)	(mm)	(mm)	(kg)	(kN)	(kg)
KM 634-0.25	0,25	420	90	460	1470	170	13	4000
KM 634-0.35	0,35	500	135	590	1950	225	16	5000
KM 634-0.50	0,50	500	170	650	1985	250	15	5000

Reinforced logging grapple KM 634S

Type	Capacity	Width E	min. Log-Ø D2	max. Log-Ø D1	Opening A max.	Weight	Closing force	Load capacity
	(m ²)	(mm)	(mm)	(mm)	(mm)	(kg)	(kN)	(kg)
KM 634S-0.40	0,40	510	135	590	1950	270	16	6000
KM 634S-0.50	0,50	510	170	650	1985	275	16	7000
KM 634S-0.70	0,70	590	110	870	2570	530	15	8000

Accessories

Type	Description
KM 06 F173-35	recommended KINSHOFER rotator for KM 634-0.25
KM 10 F173-35/1	recommended KINSHOFER rotator for KM 634-0.35
KM 10 F173-45	recommended KINSHOFER rotator for KM 634S
KM 10 F173-52	recommended KINSHOFER rotator for KM 634S

Requirements of truck crane

Operating pressure at oil flow:

max. 24 MPa (240 bar) at 25 - max. 75 l/min

⚠ **Mind the pressure!**

Technical drawings

